

AVISTA pace GER SAE 10W-40

Optimally adapted car engine oil (petrol, diesel). Particularly developed for older Daimler models.

APPLICATION

- car, petrol, diesel
- hybrid cars
- may be suitable for engines with an additional gas tank (please observe the respective OEM specifications)

CHARACTERISTICS / APPLICATION BENEFITS

- low evaporation loss
- good oxidation stability
- piston cleanliness
- outstanding cleaning and dispersion properties
- prevents oil inspissation

APPROVALS

API SN
MB-Approval 229.3

SPECIFICATIONS

ACEA A3/B4
A3/B3
Renault RN 0700 / 0710
VW 505 00 / 501 01

RECOMMENDATIONS

Peugeot PSA B71 2300 (2014)

TYPICAL CHARACTERISTICS

(The given data are typical data.)

Parameter	Method	Unit	
SAE Class	SAE J 300		10W-40
Density 15 °C	DIN EN ISO 12185	g/cm ³	0.845 – 0.885
Kin. Viscosity @ 100 °C	ASTM D7279	mm ² /s	13.3 – 14.7
Viscosity Index	ASTM D2270		min. 143
Total Base Number	ASTM D2896	mg KOH/g	10.0 – 12.4
Dyn. Viscosity @ -25 °C	ASTM D5293	mPa*s	max. 7,000
Flash Point COC	DIN ISO 2592	°C	min. 200
Pour Point	ASTM D7346	°C	max. -36

We reserve the right to change the general characteristics of our product so that our customers can benefit from the latest technological advances. (VS-Number 6)